# Distressed Medieval Grey



## PRODUCT DETAILS

| | |
|---|---|
| **Product Code** | DX4 |
| **Construction** | Engineered 3 Layer |
| **Specie** | European Oak |
| **Type** | Plank |
| **Dimensions** | 14 × 190 mm × Fixed, Long |
| **Surface** | Brushed |
| **Finish** | UV Oil |
| **Grade** | Rustic |
| **Profile** | Tongue & Groove · Micro Bevel |

## TECHNICAL CRITERIA

| | |
|---|---|
| **Certifications** | FSC, CE / UKCA |
| **Hardness (Janka)** | N/A |
| **Formaldehyde** | E1 |
| **PCP** | PCP Free |
| **Thermal Resistance** | N/A |
| **Fire Rating** | Dfl-s1 |
| **Slip Resistance** | N/A |

## INSTALLATION METHODS

| | |
|---|---|
| **Glue Down** | Recommended |
| **Nailed / Screwed** | Plank Only |
| **Floated** | Recommended |
| **Underfloor Heating** | Suitable With Conditions |

## GRADING: RUSTIC

A rustic grade celebrating the natural character of the timber, with abundant knots, colour variation and filled checks. Heartwood and sapwood appear along the edges. As a natural product, appearance varies from plank to plank and between batches.

## IMPORTANT INSTALLATION GUIDANCE

Installation is taken as acceptance of the goods and must be carried out by a competent installer to the relevant national standard, such as BS 8201. Inspect all goods before fitting.

Do not cover a newly installed floor with a non-breathable material for more than one week; trapped moisture can damage the surface, especially over underfloor heating.

© 2026 Nubio Group. All information was correct at the time of publication; the company reserves the right to change this specification at any time without notice. Photographs are illustrative only and may vary slightly.

**Showroom & Support**

193 Watford Road, Croxley Green, Rickmansworth, WD3 3EH

Tel: +44 (0)20 8087 4207 | Email: info@nubiogroup.com