Catalan Rustic Oak



PRODUCT DETAILS

Product Code	EN14342-2013
Construction	Engineered 3 Layer
Specie	European Oak
Type	Plank
Dimensions	14 × 190 mm × Fixed, Long
Surface	Brushed
Finish	UV Oil
Grade	Rustic
Profile	Tongue & Groove · Micro Bevel

TECHNICAL CRITERIA

Certifications	FSC, CE / UKCA
Hardness (Janka)	N/A
Formaldehyde	E1
PCP	PCP Free
Thermal Resistance	N/A
Fire Rating	Dfl-s1
Slip Resistance	N/A

INSTALLATION METHODS

Glue Down	Recommended
Nailed / Screwed	Plank Only
Floated	Recommended
Underfloor Heating	Suitable With Conditions

GRADING: RUSTIC

A rustic grade celebrating the natural character of the timber, with abundant knots, colour variation and filled checks. Heartwood and sapwood appear along the edges. As a natural product, appearance varies from plank to plank and between batches.

IMPORTANT INSTALLATION GUIDANCE

Installation is taken as acceptance of the goods and must be carried out by a competent installer to the relevant national standard, such as BS 8201. Inspect all goods before fitting.

Do not cover a newly installed floor with a non-breathable material for more than one week; trapped moisture can damage the surface, especially over underfloor heating.

© 2026 Nubio Group. All information was correct at the time of publication; the company reserves the right to change this specification at any time without notice. Photographs are illustrative only and may vary slightly.

Showroom & Support

193 Watford Road, Croxley Green, Rickmansworth, WD3 3EH

Tel: +44 (0)20 8087 4207 | Email: info@nubiogroup.com