# Natural Brushed Oak



## PRODUCT DETAILS

| | |
|---|---|
| **Product Code** | HB1426P |
| **Construction** | Engineered 2 Layer |
| **Specie** | European Oak |
| **Type** | Herringbone |
| **Dimensions** | 15 × 90 mm × Fixed |
| **Surface** | Brushed |
| **Finish** | Natural Oil |
| **Grade** | Character |
| **Profile** | Tongue & Groove · Micro Bevel |

## TECHNICAL CRITERIA

| | |
|---|---|
| **Certifications** | FSC, CE / UKCA |
| **Hardness (Janka)** | N/A |
| **Formaldehyde** | E1 |
| **PCP** | PCP Free |
| **Thermal** | N/A |
| **Fire Rating** | Dfl-s1 |
| **Slip Resistance** | N/A |

## INSTALLATION METHODS

| | |
|---|---|
| **Glue Down** | Required |
| **Nailed / Screwed** | No |
| **Floated** | No |
| **Underfloor Heating** | Suitable With Conditions |

## GRADING: CHARACTER

A characterful grade rich in natural features — knots, colour variation, grain movement and filled checks are all part of its appeal. Sapwood is permitted. As a natural product, appearance varies markedly between planks.

## IMPORTANT INSTALLATION GUIDANCE

Installation is taken as acceptance of the goods and must be carried out by a competent installer to the relevant national standard, such as BS 8201. Inspect all goods before fitting.

Do not cover a newly installed floor with a non-breathable material for more than one week; trapped moisture can damage the surface, especially over underfloor heating.

© 2026 Nubio Group. All information was correct at the time of publication; the company reserves the right to change this specification at any time without notice. Photographs are illustrative only and may vary slightly.

**Showroom & Support**

193 Watford Road, Croxley Green, Rickmansworth, WD3 3EH

Tel: +44 (0)20 8087 4207 | Email: info@nubiogroup.com