



PRODUCT DETAILS

Product Code	Nutmeg
Construction	Engineered 2 Layer
Specie	European Oak
Type	Herringbone
Dimensions	15 × 90 mm × Fixed
Surface	Brushed
Finish	Natural Oil
Grade	Character
Profile	Tongue & Groove · Micro Bevel

TECHNICAL CRITERIA

Certifications	FSC, CE / UKCA
Hardness (Janka)	N/A
Formaldehyde	E1
PCP	PCP Free
Thermal	N/A
Fire Rating	Dfl-s1
Slip Resistance	N/A

GRADING: CHARACTER

A characterful grade rich in natural features — knots, colour variation, grain movement and filled checks are all part of its appeal. Sapwood is permitted. As a natural product, appearance varies markedly between planks.

INSTALLATION METHODS

Glue Down	Required
Nailed / Screwed	No
Floated	No
Underfloor Heating	Suitable With Conditions

IMPORTANT INSTALLATION GUIDANCE

Installation is taken as acceptance of the goods and must be carried out by a competent installer to the relevant national standard, such as BS 8201. Inspect all goods before fitting.

Do not cover a newly installed floor with a non-breathable material for more than one week; trapped moisture can damage the surface, especially over underfloor heating.

© 2026 Nubio Group. All information was correct at the time of publication; the company reserves the right to change this specification at any time without notice. Photographs are illustrative only and may vary slightly.

Showroom & Support

193 Watford Road, Croxley Green, Rickmansworth, WD3 3EH
Tel: +44 (0)20 8087 4207 | Email: info@nubiogroup.com